

EAGLE-EYE



DISPOSITIVO DI CONNESSIONE EAGLE-R100H4-0A



- ⊙ Industrial robust design and compact metal housing
- ⊙ High data speed via FDD 4G(OPTIONAL) or 3G network, 2
- ⊙ Strong electromagnetic interference Resistance
- ⊙ Heat endurance and radiation ability
- ⊙ Built-in watchdog, Multi-link detection
- ⊙ Ultra security, VPN: PPTP, L2TP, GPE, IPsec
- ⊙ High Reliability: Hardware link self-recovery
- ⊙ MIMO antenna for 4G
- ⊙ Always online, reboot automatically if disconnected to ensure continual connection
- ⊙ Support APN and VPDN wireless private network access in
- ⊙ LCP/ICMP/flow/heartbeat check, ensure network usability
- ⊙ Web/CLI/SSH/Management platform support, easy configure
- ⊙ SNMP network management, NTP support
- ⊙ Local & remote management (configuration, status, upgrade firmware)
- ⊙ Supports DHCP Server
- ⊙ Supports DNS proxy and Dynamic DNS (DDNS)
- ⊙ Supports timing operation
- ⊙ Supports LED status indication
- ⊙ Shock and vibration resistant



EAGLE-R100H4-0A Router is the internet of thing mobile broadband router and a machine to machine (M2M) industrial cellular router, which can optional works on 4G/3G cellular network to provide reliable, secure and high speed mobile connectivity with VPN supported. The R100 is powerful and programmable industrial mobile router with high performance, small, compact and hardened mechanical design, it allows you to easily integrate it into your system, and is suitable to be used in the application where space is critical factors, such as intelligent transportation system, telemetry, ATM, Vending machine and video surveillance etc.

WLINK WL-R100 equips a single Ethernet LAN port and one serial port, VPN features also can be configured in WLINK router, allowing you to utilize virtual private network service through a 4G/3G wireless router and built for stresses and workload of a modern industrial or commercial environment.

Setting up the WLINK cellular R100 router is quick and easy - simply insert your 4G SIM card into the SIM card slot, connect the antennas and power up the equipment. In order to connect to the internet you simply need to enter the correct APN settings in the web setting interface and the router will then connect and provide high speed 4G mobile broadband internet.



Specification			
Supports Mobile Network	<ul style="list-style-type: none"> ⊙ FDD / TDD 4G ⊙ DC-HSPA+/HSPA+/HSPA/HSDPA/WCDMA/UMTS ⊙ EDGE/GPRS ⊙ CDMA2000 EVDO/CDMA 1X 	Ethernet Standard	<ul style="list-style-type: none"> ⊙ IEEE 802.3 ⊙ IEEE 802.3u
Interface	<ul style="list-style-type: none"> ⊙ 1x10/100Mb LAN interface ⊙ 1x RS-232 console port(optional) ⊙ 2x SMA-K antenna interface ⊙ 1x Standard SIM/R-UIM interface ⊙ 1x Standard DC power interface 	LED instruction	<ul style="list-style-type: none"> ⊙ Net ⊙ LAN ⊙ PWR
Route protocol	<ul style="list-style-type: none"> ⊙ Static route ⊙ RIPv2/OSPF dynamic route 	Power supply	<ul style="list-style-type: none"> ⊙ 5 ~ 32VDC
Device management	<ul style="list-style-type: none"> ⊙ Local or remote web browser (IE v8 or above) ⊙ CLI/Telnet command ⊙ M2M management platform (optional) ⊙ SSH configure (optional) 	VPN	<ul style="list-style-type: none"> ⊙ IPSec ⊙ PPTP/L2TP client ⊙ GRE/IPIP
Firewall & Filter	<ul style="list-style-type: none"> ⊙ IP packet/Domain/MAC filter ⊙ NAT ⊙ DMZ 	Other	<ul style="list-style-type: none"> ⊙ Dimension: 78.5mm x 59mm x 23.5mm (not including antenna) ⊙ Weight: 150g ⊙ Operation temperature: -30 ~ +70 degree ⊙ Store temperature: -40 ~ +85 degree ⊙ Related humidity: <95% (non-condensing) ⊙ Guarantee: one year